



Color: ■ orange

Electrical data		
Rated current		30 A

Material data		
Color		orange
Material group		I
Insulation material (main housing)		Polyamide (PA66)
Flammability class per UL94		V0
Fire load		0.065 MJ
Weight		12.2 g

Commercial data		
Product Group		1 (Rail Mounted Terminal Blocks)
PU (SPU)		50 (10) pcs
Packaging type		Box
Country of origin		DE
GTIN		4044918754712
Customs tariff number		85366990990

Product Classification		
UNSPSC		39121421
eCl@ss 10.0		27-14-11-40
eCl@ss 9.0		27-14-11-40
ETIM 9.0		EC000489
ETIM 10.0		EC000489
ECCN		NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Environmental requirements	
Processing temperature (min.)	-35 °C
Processing temperature (max.)	85 °C
Processing temperature	-35 ... +85 °C
Continuous operating temperature from	-60 °C
Continuous operating temperature up to	105 °C
Continuous operating temperature	-60 ... +105 °C

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 282-440	

Documentation			
Bid Text			
282-440	19.02.2019	xml 2.50 KB	
282-440	28.04.2017	doc 23.50 KB	

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 282-440 	EPLAN Data Portal 282-440 
	WSCAD Universe 282-440 
	ZUKEN Portal 282-440 